

ANTI SKINNING SPRAY MATERIAL SAFETY DATA SHEET

I. Product & Company Identification

Product name: TRU NOX ANTI-OXIDANT SPRAY (Anti Skinning Spray)

Supplier: Intaglio Printmaker

9 Playhouse Court

62 Southwark Bridge Road

London SEI 0AT

Tel: +44 (0) 207 928 2633

Email: info@intaglioprintmaker.com

2. Composition / Information on Ingredients

Ingredients: Low Boiling Point Hydrogen Treated Naptha-Naptha(Petroleum)
 Hydrodesulphurized Heavy 80-95%

CAS: 64742-82-1

EINECS: 265-185-4

[-] R10; [N] R51/53; [Xn] R65; [Xi] R66;

3. Hazards Identification

- Main hazards: Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
 environment.
- Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

4. First Aid Measures

Symptoms

- Skin contact: There may be irritation and redness at the site of contact.
- Eye contact: There may be irritation and redness. Corneal burns may occur.
- **Ingestion:** Nausea and stomach pain may occur. There may be vomiting. There may be loss of consciousness. Convulsions may occur.
- Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. There may be loss of consciousness. Convulsions may occur.

Actions

- **Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- **Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination
- **Ingestion:** Do not induce vomiting. If conscious, give I pint of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

Email: info@intaglioprintmaker.com www.intaglioprintmaker.com



5. Fire-Fighting Measures

- Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder.
- Exposure hazards: In combustion emits toxic fumes.
- **Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. Accidental Release Measures

- **Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.
- Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

7. Handling and Storage

- **Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden. Avoid direct contact with the substance.
- **Storage conditions:** Store in cool, well-ventilated area. Keep away from sources of ignition. Keep container tightly closed.

8. Exposure Controls / Personal Protection

- Engineering measures: Ensure there is sufficient ventilation of the area.
- **Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.
- Hand protection: Protective gloves.
- **Eye protection:** Safety goggles.
- **Skin protection:** Protective clothing with elasticated cuffs and closed neck. Boots made of PVC. Ensure safety shower is to hand.

9. Physical and Chemical Properties

• State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Insoluble

• Flash point °C: 38

10. Stability and Reactivity

- **Stability:** Stable under normal conditions.
- Conditions to avoid: Sources of ignition.
- Materials to avoid: Oxidising agents.
- Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide and carbon monoxide.

11. Toxicological Information

• Ingredients: Low Boiling Point Hydrogen Treated Naptha-Naptha(Petroleum) Hydrodesulphurized Heavy



12. Ecological Information

- Ingredients: Low Boiling Point Hydrogen Treated Naptha-Naptha(Petroleum) Hydrodesulphurized Heavy//eco
- Mobility: Insoluble in water.
- Persistence and degradability: No data available.
- Bioaccumulative potential: No data available.
- Other adverse effects: Toxic to aquatic organisms.

13. Disposal Considerations

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. Transport Information

ADR / RID

UN no: 1993ADR Class: 3Hazard ID no: 30

Labelling: 3

• Shipping name: FLAMMABLE LIQUID, N.O.S.

IMDG / IMO

• UN no: 1993

• Class: 3

Packing group: III

EmS: F-E,S-E

• Marine pollutant: .

• Labelling: 3

IATA / ICAO

• UN no: 1993

Class: 3

Packing group: III

Packing instructions: 310

Quantity: 220 L

Labelling: 3

15. Regulatory Information

Hazard symbols:

Harmful

Dangerous to the Environment





Risk phrases:

- R10: Flammable.
- R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65: Harmful: may cause lung damage if swallowed.
- R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases:

• \$1/2: Keep locked up and out of the reach of children.

Intaglio printmaker

Email: info@intaglioprintmaker.com www.intaglioprintmaker.com



- S29/56: Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- S36: Wear suitable protective clothing.
- S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. Other Information

Risk phrases used in S.2:

- R10: Flammable.
- R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65: Harmful: may cause lung damage if swallowed.
- R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.