

Graphic Etching Inks
MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 4, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Oil Base Extender	1911

SECTION II - HAZARDOUS INGREDIENTS

None

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Oil Base Extender

MANUFACTURERS CODE:
1911

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:

Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.