

Graphic Etching Inks
MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Dark Brown	545

SECTION II - HAZARDOUS INGREDIENTS

.0006 Lead Acetate
.0001 Mixed Aryl Amines

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Brown	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Dark Brown

MANUFACTURERS CODE:
545

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Burnt Umber	603

SECTION II - HAZARDOUS INGREDIENTS

.0006 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Burnt Umber

MANUFACTURERS CODE:
603

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Burnt Sienna	753

SECTION II - HAZARDOUS INGREDIENTS

.0002 Lead Acetate
.01 Hypothiolate - wetting agent

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Burnt Sienna

MANUFACTURERS CODE:
753

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Yellow Ochre	1028

SECTION II - HAZARDOUS INGREDIENTS

.0004 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Yellow Ochre

MANUFACTURERS CODE:
1028

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Raw Sienna	1055

SECTION II - HAZARDOUS INGREDIENTS

.0545 Hypothiolate
.0411 Mixed Solvent TRPS
.0010 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Sienna	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Raw Sienna

MANUFACTURERS CODE:
1055

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Raw Umber	1717

SECTION II - HAZARDOUS INGREDIENTS

.0001 Mixed Aryl Amine
.02 Hypothiolate
.01 Mixed Solvent
.0002 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Umber	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Raw Umber

MANUFACTURERS CODE:
1717

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Sepia	2265

SECTION II - HAZARDOUS INGREDIENTS

.0004 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Sepia

MANUFACTURERS CODE:
2265

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Violet	2334

SECTION II - HAZARDOUS INGREDIENTS

.0004 Lead Acetate
.0018 TRPS

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Violet	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Violet

MANUFACTURERS CODE:
2334

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Indian Red	2341

SECTION II - HAZARDOUS INGREDIENTS

.0001 Lead Acetate
.0044 Mixed Solvent TRPS
.0005 Mixed Aryl Amines
.0044 Hypothiolate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Red	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Indian Red

MANUFACTURERS CODE:
2341

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Midnight Blue	579

SECTION II - HAZARDOUS INGREDIENTS

.01 Cobalt Tallate
.004 Mineral Oil
.0013 Hypothiolate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Blue	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Midnight Blue

MANUFACTURERS CODE:
579

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Violet	2314

SECTION II - HAZARDOUS INGREDIENTS

.0094 TRPS
.0001 Mixed Aryl Amine
.0011 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Violet	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Violet

MANUFACTURERS CODE:
2314

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Thalo Turquoise	2337

SECTION II - HAZARDOUS INGREDIENTS

.0010 Hypothiolate
.0006 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Turquoise	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Thalo Turquoise

MANUFACTURERS CODE:
2337

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Thalo Blue Green Shade	2343

SECTION II - HAZARDOUS INGREDIENTS

.02 Hypothiolate
.0002 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:	Blue	

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:

Oil Base Ink

TRADE NAME:Graphic Etching Thalo Blue
Green Shade**MANUFACTURERS CODE:**

2343

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:

Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Green	577

SECTION II - HAZARDOUS INGREDIENTS

.001 Hypothiolate
.006 Naphthenate
.004 Mineral Spirits

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Green

MANUFACTURERS CODE:
577

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Thalo Viridian	2333

SECTION II - HAZARDOUS INGREDIENTS

.008	Hypothiolate
.001	Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Thalo Viridian

MANUFACTURERS CODE:
2333

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Deep Forest Green	2372

SECTION II - HAZARDOUS INGREDIENTS

.003	Hypothiolate
.0001	Lead Acetate
.008	Cobalt Tallate
.0056	Mineral Spirits
.001	Mixed Aryl Amines

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Deep Forest Green

MANUFACTURERS CODE:
2372

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching Orange	2292

SECTION II - HAZARDOUS INGREDIENTS

.0081	TRPS
.0009	Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching Orange

MANUFACTURERS CODE:
2292

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.

MATERIAL SAFETY DATA SHEET
(For Printing Ink and Related Materials)

Date: July 2, 2014

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

SUPPLIED BY: Intaglio Printmaker
9, Playhouse Court
62 Southwark Bridge Road
London SE1 0AT

EMERGENCY PHONE: 020 7928 2633

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Oil Base Ink	Graphic Etching White	1000

SECTION II - HAZARDOUS INGREDIENTS

None

SECTION III - PHYSICAL DATA

Boiling Range:	200 degrees F	Type of Odor:
Vapor Density:	Heavier than air	Evaporation Rate: Slower than ether
Liquid Density:		Percent Volatile Wt: N/A
Appearance:		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:
Oil Base Ink

TRADE NAME:
Graphic Etching White

MANUFACTURERS CODE:
1000

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.