Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200 Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List) Acrylic Screen Printing Ink (46210-46212,4620-4637,46410- 46412,4640-4669,46610-46612,4660-4689)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
Section I Manufacturer's Name Speedball Art Products, LLC	Emergency Telephone Number 704-838-1475
Address (Number, Street, City, State, and ZIP Code) 2301 Speedball Road Statesville, NC 28677 USA	Telephone Number for Information 704-838-1475
Date Prepared: January 2, 2013	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits	%(optional)
			Recommended	
VOC: 158-239 grams per litre (1.32-1.99 lbs. per gallon)				
Product labeling conforms to ASTM D-4236 Approved for the	AP seal as ne	r the Art & Craft]	Materials Institu	ite Inc
Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as				
per intended usage. DO NOT DEVIATE FROM INTENDED U	-		·····	, ,

Section III - Physical/Chemical Characteristics

Boiling Point	212°F-369°F	Specific Gravity ($H_2O = 1$)	1.02-1.4
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Colored semi-pastte with low odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A		1	I
Special Fire Fighting Procedures			
Wear self-contained breathing apparatus (I gear.	pressure-demand MSHA/NIOSH approved	l or equivalent) ar	nd full protective

(Reproduce locally)

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid Onset of decomposition is 350°F	
Incompatibility (Materials to Avoid) N/A				
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen				
Hazardous Polymerization	May Occur	Will Not Occur ✔	Conditions to Avoid N/A	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?	
	N/A	N/A	N/A	
Health Hazards (Acute and N/A	l Chronic)			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?	
N/A	N/A	N/A	N/A	
Signs and Symptoms of Exposure N/A				
Medical Conditions Generally Aggravated by Exposure None known				
Emergency and First Aid Procedures				
Contact with eyes may cause slight irritation: Flush with water.				

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Keep from freezing-product may coagulate
Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type) None required with adequate ventilation & normal usage conditions.				
Ventilation	Local Exhaust N/A	Special N/A		
	Mechanical (General) N/A	Other N/A		
Protective Gloves Impervious Eye Protection Safety Glasses or goggles				
Other Protective Clothing or Equipment N/A				
Work/Hygienic Practices Use protective cream where excessive skin contact is likely.				