

# LEFRANC BOURGEOIS CHARBONNEL ULTRAFLEX ETCHING GROUND

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878  
Issue date: 27/01/2023 Revision date: 27/01/2023 Supersedes version of: 27/08/2019 Version: 5.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : LEFRANC BOURGEOIS CHARBONNEL ULTRAFLEX ETCHING GROUND  
UFI : S55K-7X8K-8006-8TNV  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Intaglio Printmaker Ltd  
9 Playhouse Court  
62 Southwark Bridge Road  
London  
SE10AT

Phone: 02079282633

Email: info@intaglioprintmaker.com

#### 1.4. Emergency telephone number

Emergency number : +33 2 43 83 83 00 (Monday- Thursday: 8:00-12:00 13:30-16:00 , Friday: 8:00-12:00 CET  
Language French); 02079282633 Monday-Friday: 10:00-18:00 GMT Language English)

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
France	ORFILA		+33 1 45 42 59 59	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

Country	Organisation/Company	Address	Emergency number	Comment
Luxembourg	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, or German
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (oral), Category 4	H302
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhal.), Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: Gum turpentine oil, Linalool, (R)-p-mentha-1,8-diene; d-limonene, PINENES (ALPHA OR BETA), Laevo limonene, B-PINENE

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.  
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 - Use only outdoors or in a well-ventilated area.  
P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a doctor if you feel unwell.  
P331 - Do NOT induce vomiting.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Child-resistant fastening  
Tactile warning

: Applicable  
: Applicable

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Gum turpentine oil	CAS-No.: 8006-64-2 EC-No.: 932-349-8 EC Index-No.: 650-002-00-6	50 – 80	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4	3 – 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
CAMPHOR	CAS-No.: 76-22-2 EC-No.: 200-945-0	1 – 3	Flam. Sol. 2, H228 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 STOT SE 2, H371
(R)-p-mentha-1,8-diene; d-limonene	CAS-No.: 5989-27-5 EC-No.: 227-813-5 EC Index-No.: 601-029-00-7	0.1 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
PINENES (ALPHA OR BETA)	-	0.1 – 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Laevo limonene	CAS-No.: 5989-54-8 EC-No.: 227-815-6	0.1 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
B-PINENE	CAS-No.: 127-91-3 EC-No.: 204-872-5	0.1 – 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Skin Sens. 1, H317
2,6-Di-tert-butyl-p-cresol	CAS-No.: 128-37-0 EC-No.: 204-881-4	0.1 – 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER/doctor. Specific measures (see supplemental first aid instruction on this label). Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). If skin irritation or rash occurs:
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause an allergic skin reaction.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
<b>6.1.1. For non-emergency personnel</b>	
Emergency procedures	: Evacuate unnecessary personnel.
<b>6.1.2. For emergency responders</b>	
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

## 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

## 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray.  
Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.  
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

## 7.3. Specific end use(s)

No additional information available

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### 8.1.1 National occupational exposure and biological limit values

Gum turpentine oil (8006-64-2)	
France - Occupational Exposure Limits	
Local name	Térébenthine
VME (OEL TWA)	560 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	100 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
United Kingdom / Australia / New Zealand - Occupational Exposure Limits	
Local name	Turpentine
WEL TWA (OEL TWA) [1]	566 mg/m <sup>3</sup>

Gum turpentine oil (8006-64-2)	
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	850 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	150 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2,6-Di-tert-butyl-p-cresol (128-37-0)	
France - Occupational Exposure Limits	
Local name	2,6-Di-tert-butyl-p-crésol
VME (OEL TWA)	10 mg/m <sup>3</sup>
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	2,6-Di-tert-butyl-p-kresol
AGW (OEL TWA) [1]	10 mg/m <sup>3</sup> (E)
Peak exposure limitation factor	4(II)
Remark	DFG;Y;11
Regulatory reference	TRGS900
United Kingdom / Australia / New Zealand - Occupational Exposure Limits	
Local name	2,6-Di-tert-butyl-p-cresol
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup>
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

No additional information available

#### 8.2.2. Personal protection equipment

**Personal protective equipment:**

Avoid all unnecessary exposure.

**Personal protective equipment symbol(s):**



### 8.2.2.1. Eye and face protection

#### Eye protection:

Chemical goggles or safety glasses

### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear protective gloves.

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Colourless.
Odour	: strong.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 32 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 7.562 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

## 10.3. Possibility of hazardous reactions

Not established.

## 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

## 10.5. Incompatible materials

Strong acids. Strong bases.

## 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Harmful in contact with skin.  
Acute toxicity (inhalation) : Harmful if inhaled.

#### LEFRANC BOURGEOIS CHARBONNEL ULTRAFLEX ETCHING GROUND

ATE CLP (oral)	779.243 mg/kg bodyweight
ATE CLP (dermal)	1714.335 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h

#### Gum turpentine oil (8006-64-2)

LC50 Inhalation - Rat	13.7 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 11,1 - 14,8
-----------------------	---

#### 2,6-Di-tert-butyl-p-cresol (128-37-0)

LD50 oral rat	> 2930 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

#### Linalool (78-70-6)

LD50 oral rat	2790 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 2440 - 3180
LD50 dermal rabbit	5610 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 3578 - 8374

#### CAMPHOR (76-22-2)

LD50 oral	1310 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LC50 Inhalation - Rat	0.5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

#### LEFRANC BOURGEOIS CHARBONNEL ULTRAFLEX ETCHING GROUND

Viscosity, kinematic	7.562 mm <sup>2</sup> /s
----------------------	--------------------------

#### Linalool (78-70-6)

Viscosity, kinematic	5.192 mm <sup>2</sup> /s
----------------------	--------------------------

#### Laevo limonene (5989-54-8)

Viscosity, kinematic	1.011 mm <sup>2</sup> /s
----------------------	--------------------------

Potential adverse human health effects and symptoms : Harmful if swallowed,Harmful in contact with skin.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

<b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>	
LC50 - Fish [1]	> 0.57 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	0.48 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.023 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.053 mg/l Test organisms (species): Oryzias latipes Duration: '42 d'

<b>Linalool (78-70-6)</b>	
LC50 - Fish [1]	27.8 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	59 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	88.3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [2]	156.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

<b>CAMPHOR (76-22-2)</b>	
LC50 - Fish [1]	35 – 50 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	110 mg/l Test organisms (species): Pimephales promelas
EC50 96h - Algae [1]	6.951 mg/l Test organisms (species):

<b>(R)-p-mentha-1,8-diene; d-limonene (5989-27-5)</b>	
LC50 - Fish [1]	720 µg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.36 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	0.115 mg/l Test organisms (species): other:For freshwater invertebrates, species frequently include Daphnia magna or Daphnia pulex. Duration: '16 d'

<b>Laevo limonene (5989-54-8)</b>	
LC50 - Fish [1]	720 µg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	702 µg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.36 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	≈ 8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	0.904 mg/l Test organisms (species): other:For freshwater algae, species frequently include Desmodesmus subspicatus or Pseudokirchneriella subcapitata.

## 12.2. Persistence and degradability

<b>LEFRANC BOURGEOIS CHARBONNEL ULTRAFLEX ETCHING GROUND</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

#### LEFRANC BOURGEOIS CHARBONNEL ULTRAFLEX ETCHING GROUND

Bioaccumulative potential : Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods




Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
<b>14.1. UN number</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>			
Not applicable	Not applicable	Not applicable	Not applicable
			Not applicable
<b>14.4. Packing group</b>			
Not applicable	Not applicable	Not applicable Environmentally hazardous substance mark (IATA)	Not applicable
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Not applicable
No supplementary information available			

## 14.6. Special precautions for user

**Overland transport**  
No data available

**Transport by sea**  
No data available

**Air transport**  
No data available

**Inland waterway transport**  
Not applicable

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

##### France

Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism

##### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

## Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

## Denmark

Class for fire hazard	: Class II-1
Store unit	: 5 liter
Classification remarks	: R10 <H226;H302+H312+H332;H304;H315;H317;H319;H411>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

## Switzerland

Storage class (LK)	: LK 3 - Flammable liquids
CH - VOC (SR 814.018)	: 1.4422666665 %

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None.

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 2	Flammable solids, Category 2
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.

Full text of H- and EUH-statements:	
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
Acute Tox. 4 (Oral)	H302	Calculation method
Acute Tox. 4 (Dermal)	H312	Calculation method
Acute Tox. 4 (Inhalation)	H332	
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.